

Canon

Reimagine the Way You Print.

Fluorescent Pink Ink

Hits 99% of the colors in the PANTONE®
FORMULA GUIDE solid coated

Intelligent Media Handling



imagePROGRAF
GP-4000

TECHNICAL INFORMATION

imagePROGRAF
GP-4000

Printing Technology	FINE: Full-Photolithography Nozzle Engineering
Head Configuration	12-Channel Integrated Type
Nozzle Configuration	1,536 Nozzles x 12 Channels: 18,432 Total
Minimum Droplet Size	4 Picoliters per Color
Maximum Print Resolution	Up to 2400 x 1200 dpi
Ink Information	Type: Pigment-Based GP Ink Technology PFI-2100 (160 ml): FP, R, O, G, V, PBK, MBK, C, M, Y, GY PFI-2300 (330 ml): FP, R, O, G, V, PBK, MBK, C, M, Y, GY PFI-2700 (700 ml): FP, R, O, G, V, PBK, MBK, C, M, Y, GY
Print Head	PF-10 (1)
Colors	Fluorescent Pink, Red, Orange, Green, Violet, Photo Black, Matte Black, Cyan, Magenta, Yellow, Gray
Ink Tank Shipped with Printer	10 Colors + Fluorescent Pink 330 ml Ink Tank, Each Color
Hard Disk Capacity	500 GB
Printer Memory	3 GB
Printer Stand	Standard
Display	4.3" Color LCD Touch-screen
Size/Weight (with basket open)	46" (H) x 63" (W) x 39" (D)/Approx. 274 lb.
Media Feed	Front-Loading Roll Feed: One Roll, Front Output
Media Width	6" - 44" (Cut-Sheet and Roll)
Minimum Media Length	8"
Maximum Print Length*	59' (Roll Paper) 84" (Cut-Sheet)
Borderless Printing Widths	Custom Roll Width 6" - 44" with Micro Margin Technology
Media Thickness	.07 mm - .8 mm
Media Core Sizes	2" or 3" Core (with Supplied Adaptor)
Printable Margins	Roll Paper: Top: 20 mm; Bottom: 3 mm; Side: 3 mm Cut-Sheet: Top: 20 mm; Bottom: 20 mm; Side: 3 mm
Maximum Media Roll (Outer Dia.)	6.7" (170 mm)
Interfaces	Hi-Speed USB, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)**
Recommended Operating Environment*	Temperature: 59° - 86° F (15° - 30° C) Humidity: 10 - 80% (No Condensation)

Power Supply	AC 100-240 V (50-60 Hz)
Power Consumption	
Maximum:	99 W or Less
Standby:	2.0 W or Less
Power Off:	0.3 W or Less
Software	PosterArtist Lite (PC Only), Professional Print & Layout,** Free Layout plus (PC Only), Printer Driver Extra Kit (PC Only), Accounting Manager, Media Configuration Tool, Direct Print Plus (PC Only), Device Management Console, Quick Utility Toolbox, Canon PRINT Inkjet/SELPHY, Canon Print Service (Android Only), Easy-PhotoPrint Editor
Optional Software	PosterArtist (PC Only)
OS Compatibility	32-bit: Windows® 7/8.1/10 64-bit: Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008 R2, Windows® Server 2012/2012R, Windows® Server 2016, Windows® Server 2019, Mac OS X 10.12.6 or Later
User-Replaceable Items	Print Head (PF-10) Maintenance Cartridge (MC-30) Rotary Cutter (CT-07)
PANTONE® Calibrated	PANTONE PASTELS & NEONS GUIDE Coated: 97% when using Photo Paper Pro Premium Platinum with imagePROGRAF printer driver at [Poster/Photo (Fluorescent)] [Highest] (600dpi) PANTONE FORMULA GUIDE Solid Coated: 99% when using Photo Paper Pro Premium Platinum with imagePROGRAF printer driver at [Poster/Photo (Fluorescent)] [Highest] 600 dpi
Options	Multifunction Roll System (RU-43) Roll Holder Set (RH2-46)

For a complete listing of specifications, please visit usa.canon.com/largeformat.

* The maximum printable length varies, depending on the application, OS, and RIP used.

** Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

• For the temperature and humidity conditions of papers, refer to the paper's packaging or the supplied instructions.

•• Professional Print & Layout plug-in software is compatible with Adobe® Photoshop CC 2015-CC 2019 or later, Adobe Photoshop Lightroom V6.X, CC 2015-CC 2019 or later, Classic CC, Photoshop Elements 15, 2018, 2019 or later, and Canon Digital Professional 4.92 or later.



Southwest Binding & Laminating | P.O. Box 150 Maryland Heights, MO 63043-9150 | (314) 739-4400
Nationwide Toll Free Line (800) 325-3628 | Toll Free Fax (800) 942-2010 | www.swbindinglaminating.com



Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. PANTONE® is a trademark or registered trademark of PANTONE® LLC in the United States and/or other countries. As of September 27, 2021, according to professional services performed by PANTONE® under License Agreement between Canon, Inc. and PANTONE® LLC. PANTONE® PASTELS & NEONS GUIDE Coated color gamut coverage rate is 97% for GP-4000/GP-2000 when using Photo Paper Pro Premium Platinum with imagePROGRAF printer driver at [Poster/Photo (Fluorescent)] [Highest] (600 dpi). PANTONE® Colors generated may not match PANTONE®-identified standards. Consult current PANTONE® Publications for accurate color. All printer output is simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2021 Canon U.S.A., Inc. All rights reserved.
1021R1-GP-4000-SS-PDF-IH

