FD 386 Document Folder







- Processes up to 17,000 sheets per hour
- Color touchscreen control panel
- 18 pre-programmed and 27 custom folds
- Telescoping outfeed conveyor
- Dedicated multi-sheet feeder



Southwest Binding & Laminating PO Box 150 Maryland Heights, MO 63043-9150 (314) 739-4400 ~ (800) 325-3628 www.swbindinglaminating.com The Automatic FD 386 Document Folder folds up to 17,000 pieces per hour! Fully automated fold plates provide one touch set-up of the 18 pre-programmed or 27 custom folds that can be stored into memory. The FD 386 folds up to 500 sheets in as fast as 2 minutes and holds the folded pieces on its patented Telescoping Conveyor System with adjustable stacker wheels. The large full-color touchscreen control panel allows operators to walk up and start folding with little to no instruction. The optional patented Multi-Sheet Feeder allows up to 4 stapled or unstapled sheets to be folded at one time. The FD 386 can also be combined with the optional V-Stack36i Vertical Stacker, which stacks up to 22" of folded documents.



Color Touchscreen Control Panel Utilizes easily-recognized symbols in place of text



Adjustable Stacker Wheels Neatly stack different paper sizes and fold types



Optional Multi-Sheet Feeder Up to 4 stapled or unstapled sheets can be folded at once



Telescoping Conveyor System Extends from 14" to 36" in length and holds up to 500 folded pieces



Optional V-Stack36i Vertical Stacker Aligns with outfeed to vertically stack up to 22" of folded documents for further processing

OPTIONS	SPECIFICATIONS	
Multi-sheet feeder	Speed	Up to 17,000 sheets per hour, based on 11" Z-Fold
Locking cabinet		
V-Stack36i Vertical Stacker	Hopper Capacity	Up to 500 sheets 20#
	Pre-Set Folds	Pre-programmed for C, V, Z, Gate, Fold Out, and Double Parallel
	Custom Folds	Up to 27
	Paper Sizes	Min: 3.5" W x 5" L (89 x 127mm) Max: 12.25" W x 18" L (311 x 457mm)
	Dimensions - Closed Dimensions - Extended	33" L x 20" W x 19"H (838 x 508 x 483mm) 60" L x 20" W x 19" H (1524 x 508 x 483mm)
	Weight	73 lbs (33kg)
	Power	110-240VAC 50/60 Hz
	Safety Certifications	UL & CE approved

STANDARD FEATURES

Folds up to 17,000 pieces per hour Color touchscreen Telescoping conveyor system Adjustable stacker wheels 18 pre-programmed fold settings Stores up to 27 custom folds Drop-in three-roller feed system Noise reduction 6-Digit resettable & 8-Digit life counter AutoBatch™ Cross-folding guide Easy-off feed wheel shaft Seven-point fold stops for accuracy

Removable roller cover

6/2024